

Please amend the Claims as follows:

Claim 1. (Currently Amended) A fitment for a container having a top end and a first wall associated with the top end comprising:

means defining an opening through the first wall associated with the top end of the container,

a circumferential flange member,

a second wall upstanding from said flange member,

said second wall defining a conduit having entrance and exit ends through which contents of the container may be discharged,

at least said exit end of said conduit having a substantially ellipsoidal planar cross-sectional geometry having at least one major portion and at least one minor portion,

said minor portion being disposed vertically above said major portion when said fitment is affixed to the first wall of the container and the container is oriented in a direction for discharge of the contents of the container through said opening and substantially simultaneous ingress of ambient air into the container through said minor portion of said fitment, a tear away membrane disposed across and closing said conduit at a location spaced apart from said first wall associated with the top end of the container, and including pull ring means affixed to said tear away membrane thereby providing for localization of an initial tear away force applied through said pull ring.

Claim 2. (Previously Amended) The fitment of Claim 1 wherein said cross-sectional geometry of at least said exit end of said conduit has an aspect ratio of less than one.

Claim 3. (Original) The fitment of Claim 1 wherein said container and said fitment each includes a longitudinal centerplane and said centerplanes are coincident when said fitment is affixed to the top end of said container.

Claim 4. (Original) The fitment of Claim 1 and including a cap member integrally formed in hinged relationship with said wall defining said conduit.

Claim 5. (Currently Amended) The fitment of Claim 4 wherein said cap member includes first and second annular projections extending from a surface thereof, said projections being spaced apart from one another to define therebetween a void annular space, said annular space having a geometry substantially like said ellipsoidal cross-section geometry of said conduit and adapted to receive therein an outboard rim of

said second wall to thereby releasably close and seal said conduit against the passage of the contents of said container therethrough.


Claims 6-18 have been cancelled.

Claim 19. (Currently Amended) The fitment of Claim 1 wherein said circumferential flange is physically disposed internally of said container and affixed to the inner surface of the first wall associated with the top end of the container and said second wall extends from the circumferential margin of said opening outwardly of said opening to define said conduit.

Claim 20. (Previously Amended) The fitment of Claim 19 wherein said second wall upstanding from said circumferential flange member projects from said circumferential flange through said opening defined through the first wall associated with the top end of the container.

Claim 21. (New) The fitment of Claim 19 wherein said membrane is wholly disposed within said conduit and at a location within said conduit spaced apart from said opening.

Respectfully submitted,


Paul E. Hodges
Registration Number 20,972

PITTS & BRITTIAN, P.C.
P.O. Box 51295
Knoxville, Tennessee 37950-1295
(865) 584-0105 Voice
(865) 584-0104 Fax